

A Series



PulsEater® Ceramic Composition Available in E12 Ohmic values

The “A” Series non-inductive, ceramic composite resistors are designed for a variety of applications where high energy handling capabilities are crucial. These resistors are ideal for any application which is subject to surges, high peak power, or impulse energy.

Their unique design allows uniform distribution of energy throughout their structure which results in low thermal stress. The high-temperature, solvent-resistant epoxy coating carries a UL94V0 flammability rating which is suitable for almost any environment.



*AZ style is provided with dual terminal wires

FEATURES

- High Surge Energy
- Non-Inductive
- Small Size

APPLICATIONS

- Motor Drives
- Power Supplies, UPS
- Power Conversion
- In-Rush Current Limiting

SERIES SPECIFICATIONS

Series	Resistance ¹ (ohms)	P avg. ² (watts)	Impulse Voltage ³ (volts)	Energy ⁴ (joule)
AV	3.3 to 10K	2.0	1000	250
AW	4.7 to 15K	2.5	1500	400
AX	1.0 to 3.3K	3.5	1000	700
AY	2.2 to 6.8K	4.5	2000	1400
AZ	1.5 to 4.7K	5.5	2500	2800

¹E12 Standard Values ±10%; ²Free Air 40°C Ambient; ³In Air; ⁴Single Impulse

CHARACTERISTICS

Resistance Element	Bulk Ceramic
Terminals	Radial; 100% Sn solder coated radial (60/40 solder available upon request)
Coating	UL94V0, solvent resistant epoxy
Tolerance	±10% Standard
Operating Temp. Range	-55°C to 150°C
Derating	Derates linearly from 100% @ 50°C to 0% @ 150°C
Temperature Rise	100°C @ 100% rated power, 50°C ambient

Derating



Mounting clip



Dim. (mm)

Part No.	D	H	L	for Series	Color
5911E	20	23	13	AX and AY	White
5910E	25	26	15	AZ	Black

This saddle clip conforms to the configuration of Ohmite's A Series resistor to provide secure mounting. Made of a durable thermoplastic polyester, the saddle clip is designed to secure the A Series in place while safely withstanding its operating temperatures. Use (2) saddle clips per resistor for extra stability.

Surface Temperature Rise vs. Applied Power



(continued)

A Series

PulsEater® Ceramic Composition
Available in E12 Ohmic values

DIMENSIONS



Series	P avg. 2 (watts)	L max. (mm)	D max. (mm)	H max. (mm)	S norm. (mm)	Term. wire gauge (AWG)	Weight (g)
AV	2.0	15	13	22	12.5	20	3.9
AW	2.5	20	13	22	17.5	20	5.4
AX	3.5	15	21	28	12.5	18	10
AY	4.5	25	21	28	22.5	18	19
AZ	5.5	30	26		27	18	33

ORDERING INFORMATION

RoHS compliant

A W 5 6 G K E

Size Ohm Value Tolerance
 Example:
 33G = 3.3 Ohms K = 10% std.
 330 = 33 Ohms M = 20%
 331 = 330 Ohms

Standard Values

Ohmic value	Part No. Prefix Suffix	Series	Ohmic value	Part No. Prefix Suffix	Series	Ohmic value	Part No. Prefix Suffix	Series	Ohmic value	Part No. Prefix Suffix	Series
1.0 — 10GK	AV	✓	5.6 — 56GK	AV	✓	33 — 330K	AV	✓	220 — 221K	AV	✓
1.2 — 12GK	AW		6.8 — 68GK	AW	✓	39 — 390K	AW	✓	270 — 271K	AW	✓
1.5 — 15GK	AX		8.2 — 82GK	AX	✓	47 — 470K	AX	✓	330 — 331K	AX	✓
1.8 — 18GK	AY	✓	10 — 100K	AY	✓	56 — 560K	AY	✓	470 — 471K	AY	✓
2.2 — 22GK	AZ	✓	12 — 120K	AZ	✓	68 — 680K	AZ	✓	560 — 561K	AZ	✓
2.7 — 27GK			15 — 150K		✓	82 — 820K		✓	680 — 681K		✓
3.3 — 33GK	AV	✓	18 — 180K	AV	✓	100 — 101K	AV	✓	820 — 821K	AV	✓
3.9 — 39GK	AW	✓	22 — 220K	AW	✓	120 — 121K	AW	✓	1000 — 102K	AW	✓
4.7 — 47GK	AX	✓	27 — 270K	AX	✓	150 — 151K	AX	✓		AX	✓
	AY	✓		AY	✓	180 — 181K	AY	✓		AY	✓
	AZ	✓		AZ	✓		AZ	✓		AZ	✓

Check product availability at www.ohmite.com

✓ = Standard values Non-standard values subject to a minimum handling charge per item.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ohmite:

[AX33GKE](#) [AZ680KE](#) [AW561KE](#) [AY27GKE](#) [AY391KE](#) [AY390KE](#) [AW560KE](#) [AW180KE](#) [AW221KE](#) [AZ68GKE](#)
[AW471KE](#) [AW68GKE](#) [AX15GKE](#) [AY470KE](#) [AZ471KE](#) [AZ101KE](#) [AW47GKE](#) [AY270KE](#) [AZ47GKE](#) [AX330KE](#)
[AZ681KE](#) [AW121KE](#) [AX151KE](#) [AW681KE](#) [AY560KE](#) [AZ100KE](#) [AW181KE](#) [AW680KE](#) [AW120KE](#) [AX150KE](#)
[AY39GKE](#) [AW56GKE](#) [AW470KE](#) [AW220KE](#) [AX331KE](#) [AZ470KE](#) [AZ102KE](#) [AY271KE](#) [AZ121KE](#) [AY121KE](#)
[AY681KE](#) [AY102KE](#) [AZ82GKE](#) [AZ18GKE](#) [AW150KE](#) [AW82GKE](#) [AZ220KE](#) [AZ56GKE](#) [AX270KE](#) [AX390KE](#)
[AZ390KE](#) [AZ120KE](#) [AZ181KE](#) [AZ821KE](#) [AW821KE](#) [AZ561KE](#) [AY120KE](#) [AY680KE](#) [AY100KE](#) [AX47GKE](#)
[AX101KE](#) [AW270KE](#) [AY561KE](#) [AY821KE](#) [AY181KE](#) [AX10GKE](#) [AW331KE](#) [AX471KE](#) [AX68GKE](#) [AW100KE](#)
[AX56GKE](#) [AY330KE](#) [AX220KE](#) [AZ27GKE](#) [AZ391KE](#) [AX82GKE](#) [AZ330KE](#) [AX18GKE](#) [AY151KE](#) [5910E](#) [AY180KE](#)
[AY820KE](#) [AW330KE](#) [AY221KE](#) [AW391KE](#) [AZ151KE](#) [AX102KE](#) [AX470KE](#) [AY22GKE](#) [AZ15GKE](#) [AX100KE](#)
[AW271KE](#) [AX680KE](#) [AY220KE](#) [AY56GKE](#) [AW390KE](#) [AZ150KE](#) [AX681KE](#) [AY82GKE](#) [AW102KE](#)